




03 03 / 02 82 +  
10/17834

INVESTOR IN PEOPLE

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

*Stephen Hordley*

Dated 17 July 2003

**BEST AVAILABLE COPY**



# The Patent Office

04JUL02 E730814-1 001038  
P01/7700 0.00-0215421.9

The Patent Office  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference P700140GB/JG/SAC/44845

2. Patent application number  
(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Wabco Automotive UK Limited  
Beacon Works  
Texas Street  
Morley  
Leeds  
LS27 OHQ  
United Kingdom

0215421.9

5951231002

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Vehicle Air Supply System

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

WITHERS & ROGERS  
Goldings House  
2 Hays Lane  
London  
SE1 2HW

Patents ADP number (if you know it)

1776001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day / month / year)
---------	---	--

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)
-------------------------------	--

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

YES

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description 5

Claim(s)

Abstract

Drawing (s) 1 + 1

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and  
right to grant of a patent (Patents Form 7/77)

Request for preliminary examination  
and search (Patents Form 9/77)

Request for substantive examination  
(Patents Form 10/77)

Any other documents  
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

  
WITHERS & ROGERS

Date 02 July 2002

12. Name and daytime telephone number of  
person to contact in the United Kingdom

James Gray

01926 336111

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

## Vehicle Air Supply System

This invention relates to a vehicle air supply system and particularly to a system adaptable to occasionally supply large volumes of air at relatively low pressure for, for example, tyre inflation purposes.

- A typical air supply system includes a compressor, a reservoir for pressurised air, and a driver operated demand valve to forward air from the reservoir for a desired purpose, for example to operate and maintain a braking system or pneumatic suspension system.
- 10 The air supply system usually includes a dryer for compressor outlet air, and control means to take the compressor off load and regenerate the air dryer when the reservoir is at maximum pressure and the demand valve is closed. The compressor is typically taken off load by spragging a valve or by venting the compressor cylinder to atmosphere so that the compressor free wheels. Alternatively the compressor may
- 15 include a clutch engageable with the compressor drive source, usually the vehicle engine. The air dryer is regenerated by passing a volume of dry air through the desiccant in reverse, and is typically triggered as the reservoir reaches maximum pressure, and regardless of the volume of air which has been dried.
- 20 In addition to the air being used e.g. for pneumatic suspension, the system may occasionally be required to forward relatively large volumes of air, i.e. volumes greater than the volume of the reservoir, at low pressure for, for example, tyre inflation. Typically the pressure of air required for tyre inflation will not exceed 2.5 bar. In such a situation the compressor is required to operate for longer than is normally required to
- 25 fill the reservoir, and there exists the possibility that during this extended operation of the compressor the desiccant in the air dryer may become saturated especially if the air dryer is regenerated only at times when the reservoir reaches the maximum design pressure.
- 30 If however the air dryer is designed to cope with occasional demands for a large volume of air, the volume of desiccant will be very large, and the majority will be unused for

most of the time. To address such an eventuality the control means may be configured so as effect intermediate regeneration of the desiccant, that is to say before the reservoir reaches maximum pressure. However, there may exist vehicle operation modes where such an intermediate regeneration is undesirable.

5

According to the present invention there is provided an air supply system having a compressor, an air dryer, a reservoir adapted to receive air from the compressor via the air dryer, and control means operable to cause a standard regeneration of the air dryer when a predetermined system condition is met, the control means also being operable to  
10 cause an intermediate regeneration of the air dryer in advance of said predetermined system condition being met, wherein the control means are further operable to inhibit said intermediate regeneration.

In a preferred embodiment the additional control means include a governor which is  
15 adapted to cause a standard regeneration and a governor bypass adapted to cause an intermediate regeneration. In order to inhibit the intermediate regeneration the control means may be adapted so as to disable the governor bypass.

The control means is operable so as to prevent saturation of the air dryer desiccant in  
20 circumstances where the compressor is on load for an extended period of time, and thus likely to be pumping a large volume.

In a preferred embodiment the predetermined system condition is a reservoir pressure and the governor is adapted to operate when the reservoir reaches a target pressure. In  
25 such an embodiment the governor sends an off load/purge signal to the compressor and air dryer when the target pressure is reached. The signal may be a pressure signal. Preferably the pressure signal is communicated via a pressure line from the reservoir. The governor may, in a preferred embodiment, include a pressure sensitive valve in said pressure line.

30

The control means may be adapted to bypass the governor and send an off load/purge signal to the compressor and air dryer. In the case where signal is a pressure signal, the

control means may include a bypass line for the governor, a valve positioned in said bypass line and a timer adapted to open said valve. The valve may be solenoid operated. The timer is thus adapted to open said valve and thereby send an off-load purge signal after a predetermined time period has elapsed. Preferably the timer is  
5 activated and suspended response to a predetermined system condition. The timer may be responsive to, for example, reservoir pressure or the operating condition of the compressor. The timer is preferably reset after each regeneration.

In order to inhibit the intermediate regeneration there may be provided means to block  
10 or interrupt the signal to the compressor and air dryer. In the example of a pressure signal there may be provided means to block the pressure line. In an alternative embodiment the timer may be adaptable so as to prevent an intermediate regeneration. For example, the timer may be adapted so as to be suspended, or alternatively to increase the predetermined time period. In such an embodiment where the timer period  
15 is increased it will be understood that, as a result of such an increase, the desiccant may contain more moisture than would be expected to accumulate during normal use. The timer may therefore be adapted to reduce the time period between a predetermined number of regenerations subsequent to inhibiting a regeneration.

20 In yet a further embodiment the operation of the compressor may be modified after the occurrence of an inhibited regeneration in order to allow the desiccant to recover. The threshold pressure at which the compressor cuts out may be temporarily lowered, thereby permitting more regenerations to take place.

25 An embodiment of the present invention will now be described with reference to the accompanying drawing (Figure 1) which shows a schematic representation of an air supply system, generally designated 10, according to the present invention.

The air supply system 10 includes a compressor 12, an air dryer 14, a charging valve 16  
30 and a reservoir 18. The system 10 further includes a governor 20 which is sensitive to the pressure within the reservoir 18 and arranged to take the compressor off load and regenerate the air dryer desiccant when the reservoir 18 reaches a target pressure.

Regeneration of the air dryer desiccant is achieved by venting the air dryer 14 to atmosphere and flushing the desiccant with a small amount of dry air contained in a purge tank 22. In Figure 1 the purge tank 22 is shown separate from the reservoir 18, however it will be understood that the purge tank 22 can be incorporated into the reservoir 18. Finally, the air supply system 10 comprises a purge control valve 24 and a timer 26, the operation of which will be described in greater detail below.

Normal operation of the air supply system 10 is as follows. Moist compressed air from the compressor 12 is passed via conduit 28 to the air dryer 14. The moist air is dried by being passed through a desiccant bed in the air dryer 14 before being supplied to the reservoir 18 via conduit 30 and the charging valve 16, and to the reservoir 22. Pressurised air from the reservoir 18 can then be supplied via outlet conduit 32 and a demand valve (not shown). The reservoir 18 includes a pressure line 34 which is connected to the governor 20. In the embodiment shown the governor 20 includes a pressure sensitive valve 36 which is operable to supply a signal pressure via pressure line 38 from the reservoir 18 to the air dryer 14.

When the governor 20 senses via pressure line 34 that the reservoir 18 has reached a target pressure, the valve 36 moves from the position shown to pressurise line 38. The pressure signal received by the air dryer 14 takes the compressor 12 off load, opens a vent of the air dryer 14 to atmosphere and purges the desiccant with dry air from the purge tank 22. When the reservoir pressure falls below a predetermined pressure, for example when air is supplied from the reservoir 18, the valve 36 reverts to the position shown in the figure and the pressure signal to the air dryer 14 is cut off. The air dryer vent closes and the compressor 12 is brought on line to replenish the reservoirs 18, 22.

The rating of the compressor 12 and air dryer 14, and the volume of the reservoir 18 are such that, during normal operation as described above, regeneration of the desiccant takes place well before saturation is reached. However in circumstances where the compressor 12 is required to supply volumes of air in excess of those normally required to replenish the reservoir 18, intermediate regeneration of the desiccant, i.e. before the reservoir target pressure is reached, is necessary to prevent saturation of the desiccant.

This intermediate regeneration is achieved by the provision of the timer 26 and purge control valve 24. The timer 26 is sensitive to the pressure in the reservoir 18 and when the reservoir pressure drops below a predetermined value the timer 26 is activated.

5 After a predetermined time interval the timer 26 operates the purge control valve 24 via a solenoid and causes it to move from the position shown in the figure. This has the effect of pressurising line 38 via a governor bypass line 40 and pressure line 34. The pressure signal received by the air dryer 14 has the effect of taking the compressor 12 off load and purging the desiccant. When the purging operation has taken place, typically a  
10 few seconds, the valve 24 reverts to its initial position and the timer 26 is reset. The loss of pressure in line 38 brings the compressor 12 on load and the supply of pressurised air to the reservoir 18 resumed.

During normal operating conditions, the desiccant is regenerated by the governor 20  
15 well in advance of the time interval required for the timer 26 to operate the purge control valve 24. In such circumstances, when the reservoir 18 reaches the target pressure and/or the governor 18 operates, the timer is suspended or reset in advance of the next drop in reservoir pressure. It will be understood that the timer governed purge cycle will repeat until the timer is suspended or reset.

20 In the embodiment shown the timer 26 is sensitive to and operated by the reservoir pressure. It will be understood that the timer 26 may be sensitive to other system parameters. For example the timer 26 may be activated when the compressor comes on load and be suspended/reset when the compressor comes off load.

25 As discussed above, the system 10 may be controlled so as to inhibit the intermediate regeneration of the air dryer 14. In one embodiment there is provided means 42 adapted to break the pressure line 38 and associated control means 44. In an alternative embodiment control means 46 may be provided which alter the operation of the timer  
30 26. For example the timer 26 may be suspended when it is determined that an intermediate regeneration is to be inhibited. Alternatively, the control means 46 may increase the time period which needs to elapse before an intermediate regeneration.






Fig. 1

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☒ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**